

"Your monitoring specialist"  
certified ISO 9001 + ISO 14001



## Crimping Line

# Micrograph laboratory **Microlab ML 3700-pc**

Tabletop laboratory with integrated mini PC for making cross-section analysis




*With the Microlab ML 3700-pc you can prepare microsections of crimped contacts in a very professional and comfortable manner.*

The Microlab product family is designed to prepare cross sections of conductor crimps and insulation crimps easily and comfortably within a few minutes. After cutting, polishing and etching of the sample, the image of the cross section can be visualized on the screen. Now a comprehensive quality check of the crimp can be performed by using the special designed image processing software X-Scan.

Equipped with a high quality 12x zoom objective the Microlab ML 3700-pc is the ideal tool to conduct quality tests quick and comfortable. The high resolution camera delivers first-class digital colour pictures which can be easily measured with the automatic function of the image processing software **X-Scan**. Automatically generated records can be used as proofs of quality. Of course, X-Scan fulfills all relevant DIN standards and OEM specifications.

### Performance features

- 🔍 **Complete micrograph laboratory** with integrated mini PC
- 🔍 Easily operated **optic with 12x zoom objective** with an outstanding combination of zoom and resolution
- 🔍 **First-class digital colour camera USB 3.0** with CMOS Sensor and 5.0 megapixel resolution
- 🔍 Well suited for cross sections from **0.1 to 10 mm<sup>2</sup>** (AWG 28 – AWG 10)
- 🔍 Comfortable **analysis software X-Scan**



1



C-tec Cable technologies GmbH & Co.KG  
Ilztalstraße 11 Tel.: +49 (0) 8554 – 94 23 9-0  
D-94513 Schönberg Fax: +49 (0) 8554 – 94 23 9-20

eMail: [info@cable-tec.net](mailto:info@cable-tec.net)  
HP: [www.cable-tec.net](http://www.cable-tec.net)



*"Your monitoring specialist"*  
certified ISO 9001 + ISO 14001

## Crimping Line

### Performance features in detail

- ⊗ **Complete system**, integrated ergonomically and functionally in a MDF board laminated with stainless steel
- ⊗ With **integrated mini PC**, monitor, mouse, keyboard and license for Windows 10 prof.
- ⊗ High quality **optic with 12x zoom objective** and **convenient focusing** (coarse and fine adjustment)
- ⊗ **High performance digital colour camera** USB 3.0, 2560x1920 Pixel
- ⊗ Suitable for small and medium contact sizes from **0.1 to 10 mm<sup>2</sup>**
- ⊗ Standard terminal holder for **cross sections up to 6 mm<sup>2</sup>** (further sizes available on request)
- ⊗ Long-life **LED illumination** at the microscope
- ⊗ Energy saving **working lamp** for the Cutting-/Grinding unit
- ⊗ Fitting gas tight mount for 7 calibration gauges
- ⊗ Appropriate tool set for the sample preparation
- ⊗ With comfortable **analysis software X-Scan**
- ⊗ Software calibration based on traceable standards incl. calibration certificate
- ⊗ Cross-sectioning of the sample can be carried out **without any disturbance** of the terminal and cable stranding
- ⊗ Optional: integrated **Cut Camera (VCS)** for exact cut control, easily operated by touch display
- ⊗ Optional: ancillary lens 0.5x or 0.25x for extended applications



Optics with camera and integrated PC



Cut control with an optional Cut Camera (VCS)

### Specifications

⊗ Type	ML 3700-pc
⊗ Voltage supply	100 – 240 VAC 50/60 Hz
⊗ Smallest extension (15" monitor)	24x
⊗ Largest extension (15" monitor)	288x
⊗ Smallest crimp height for a full screen	0.25 mm
⊗ Largest crimp height for a full screen	8.0 mm
⊗ Measurement resolution µm per pixel	13 - 7.31- 5.17 - 3.72 - 3.0 - 2.45 - 2.10 - 1.84 - 1.64 - 1.47 - 1.34 - 1.23 - 1.14 - 1.06
⊗ Optical zoom grades	0.58 - 1.0 - 1.5 - 2.0 - 2.5 - 3.0 - 3.5 - 4.0 - 4.5 - 5.0 - 5.5 - 6.0 - 6.5 - 7.0
⊗ Camera resolution	2560 x 1920 Pixel
⊗ Camera connection	USB 3.0 port
⊗ Object illumination	Long-life LED ring light for true colour pictures
⊗ Fine polishing	electro chemical
⊗ Cross section sizes standard	0.1mm <sup>2</sup> - 10mm <sup>2</sup> (AWG 28 – AWG 10)
⊗ Recommended temperature	22°C +/- 5°
⊗ Dimensions (W x D x H)	1200mm x 630mm x 670mm
⊗ Weight	38 kg