

EUROTE ST 50 & 100	EUROTE ST 200	EUROTE ST 300	EUROTE ST 400	EUROTE ST 500	EUROTE ST 600
Class ISO 7500-1	0,5 From 0,5% to 100% FS				
Maximum load	50 kN 100 kN	200 kN	250 kN 300 kN	400 kN	500 kN 600 kN
Load measurement	Universal strain-gage load cell (tension-compression)				
Force resolution	0,0001 kN				
Load cell Repeatability	0,03%				
Horizontal clearance	500 mm	650 mm	720 mm		
Vertical clearance , distance between standard gripping heads	Ajustable between 0 and 1300 mm		Ajustable between 0 and 1400 mm		
Displacement speed	From 0,001 to 1000,00 mm/min (other speeds on demand)		From 0,001 to 500,00 mm/min		
Displacement measurement	Encoder (digital pulse sensor)				
Displacement resolution	0,1 micron				
GENERAL CHARACTERISTICS					
Dimensions: Testing frame (m m)	1020 x 650 x 2450mm (width x depth x height)		1200 x 650 x 2900 mm	1550 x 690 x 2900 mm (width x depth x height)	
Approx weight (without gripping heads)	1000 kg	1200 kg	1400 kg	2900 kg	
Power supply	3x 380 V + N+ T, 50/60 Hz				